

# ReSound ENZO 3D™



ET 98-DW

## Product Description

ReSound ENZO 3D is a complete super power hearing solution. It is capable of providing the industry's highest amplification without feedback. It offers exceptional clarity and sound quality, and balances improved hearing in noise with preserved access to environmental sounds.


The Smart Range C platform in ReSound ENZO 3D supports our 5th generation of 2.4 GHz wireless technology. This allows ear-to-ear communication along with direct connection to the new ReSound Smart 3D™ app, and lets the hearing aids connect wirelessly to iPhone, iPad, iPod touch, and select Android models\* via Bluetooth 4.0.

It also includes the industry first ReSound Assist, which brings you even closer to your clients by offering fine-tuning and hearing aid update opportunities remotely via secure cloud technology.

The ReSound ENZO 3D SP BTE hearing aids are iSolate™ nanotech coated for optimum durability and meet the IP58 classification for ingress protection.

\*See more on [resound.com/compatibility](http://resound.com/compatibility)

### Fitting Range



Model	ET998-DW	ET798-DW	ET598-DW
<b>Device Configurations</b>			
Battery size	675		
Colors available	10		
<b>Audiological Features</b>			
WARP compression (WDRC) - number of channels	17	14	12
Binaural Directionality III	●	-	-
Spatial Sense	●	-	-
Binaural Directionality	-	●	-
Natural Directionality II	●	●	●
Directional Mix Processor	●	●	●
-Adjustable directional mix	●	-	-
Synchronized SoftSwitching	●	●	-
SoftSwitching	●	●	●
Autoscope Adaptive Directionality	●	-	-
Multiscope Adaptive Directionality	-	●	-
Adaptive Directionality	-	-	●
Binaural Environmental Optimizer II	●	-	-
Environmental Optimizer	-	●	-
NoiseTracker II	●	⊙	○
Expansion	●	⊙	○
Windguard	●	⊙	○
Sound Shaper	●	●	●
DFS Ultra II	●	●	●
-Music Mode	●	●	●
LowFrequency Boost	●	⊙	○
Amplification strategy (WDRC/Semi-Linear/Linear)	●	●	⊙
Synchronized Acceptance Manager	●	●	●
Tinnitus Sound Generator	●	●	●
<b>Functional Features</b>			
Synchronized Push Button	●	●	●
Synchronized Volume Control	●	●	●
Smart Start	●	●	●
Phone Now	●	●	●
Comfort Phone	●	●	●
Ear to Ear Communication	●	●	●
Direct audio streaming (Made for iPhone)	●	●	●
ReSound TV Streamer 2, Remote Control 2, Phone Clip+, Micro Mic and Multi Mic	●	●	●
ReSound Control™ app (Phone Clip+ is required)	●	●	●
ReSound Smart 3D™ app	●	●	●
<b>ReSound Assist</b>			
Remote Fine Tuning	●	●	●
Remote Firmware Updates	●	●	●
<b>Fitting Features</b>			
Fitting Software Smart Fit™ 1.1 or higher	●	●	●
Fully Flexible Programs	4	4	4
Auto DFS	●	●	●
Onboard Analyzer II	●	●	●
Wireless Fitting with Noahlink Wireless	●	●	●

○ Basic

⊙ Advanced

● Ultimate



ReSound ENZO 3D is compatible with iPhone 7 Plus, iPhone 7, iPhone 6s Plus, iPhone 6s, iPhone 6 Plus, iPhone 6, iPhone SE, iPhone 5s, iPhone 5c, iPhone 5, iPad Pro (12.9-inch), iPad Pro (9.7-inch), iPad Air 2, iPad Air, iPad mini 4, iPad mini 3, iPad mini 2, iPad mini, iPad (5th generation), iPad (4th generation), iPod touch (6th generation) and iPod touch (5th generation) using iOS 8.X or later.

© 2017 GN Hearing A/S. All rights reserved. Apple, the Apple logo, iPhone, iPad Pro, iPad Air, iPad mini, iPad and iPod touch are trademarks of Apple Inc., registered in the U.S. and other countries. Android is a trademark of Google Inc. The Bluetooth word mark and logos are registered trademarks owned by the Bluetooth SIG, Inc.




# Technical Specifications

## ET 98-DW


		IEC 60118-0 IEC 711 Ear simulator	IEC 60118-7 ANSI S3.22 2cc coupler	
Reference test gain (60 dB SPL input)	1600 Hz/HFA	61	54	dB
Full-on gain (50 dB SPL input)	Max. 1600 Hz/HFA	86 75	83 69	dB
Maximum output (90 dB SPL input)	Max. 1600 Hz/HFA	145 136	141 131	dB SPL
Total harmonic distortion	500 Hz 800 Hz 1600 Hz	3.5 1.0 1.2	4.0 0.7 0.9	%
Telecoil sensitivity (1 mA/m input)	Max.	116	-	
HFA - SPLIV @ 31.6 mA/m (ANSI)	HFA	-	116	dB SPL
Full-on telecoil sensitivity @ 1mA/m	1600 Hz/HFA	106	101	
Equivalent input noise		22	26	dB SPL
1/3 Octave Equivalent input noise, w/o Noise reduction		9	-	dB SPL
Frequency range (DIN 45605/ANSI)		100-5830	100-5860	Hz
Current drain		1.3/1.7	1.3/3.3	mA

Patents pending

Maximum Output (OSPL 90)



Maximum Output (OSPL 90)




Notes:  
O.E.S. = Occluded Ear Simulator  
2cc = 2 cm<sup>3</sup> coupler


Basic settings:  
Full-on Gain, Reference Test Gain  
MPO = Maximum Power Output  
Maximum Band Width

All specifications are subject to change without notice

Full-On and Reference Test Gain




Full-On and Reference Test Gain




Measured according to IEC 60118-0, Edition 3 2015-06 at 1.3V, impedance 6.2 ohms and 23°C on O.E.S. according to IEC60318-5 2006. Response on 2cc according to IEC 60118-7 2nd edition, 2005-10 and ANSI S3.22-2009 (HFA average calculated at 1,000Hz, 1,600Hz, and 2,500Hz); 0 dB SPL sound pressure equals 20µPa. All measurements without DSP and features activated unless indicated otherwise.

Input/Output Response



Full-On Telecoil Response  
Input level 10 mA/m



400740000GB-17.09-Rev.C

**ReSound A/S**  
Lautrupbjerg 7  
DK-2750 Ballerup, Denmark  
Tel.: +45 45 75 11 11  
resound.com

**United Kingdom**  
GN ReSound Ltd.  
Kirtlington Business Centre  
Portway  
Kirtlington  
Oxon OX5 3JA  
Tel.: +44 1869 352 800  
resound.com

**Australia**  
GN ReSound Pty. Ltd.  
Unit R1 Regent Park Estate  
391 Park Road  
Regent Park NSW 2143  
Tel.: 02 9743 9707  
Free call number: 1800 658 955  
resound.com

**New Zealand**  
GN ReSound (NZ) Ltd.  
Ground Floor, North Entrance  
4 Fred Thomas Drive  
Takapuna  
Auckland, 0622  
Tel.: (free) 0800 900 126  
resound.com

**Singapore**  
GN Hearing Pte. Ltd.  
2 Kallang Avenue  
#07-19 CT HUB  
Singapore - 339407  
Tel: +65 6320 9388  
resound.com

