

ReSound LiNX²



Product Description

Model 77 Behind-the-Ear (BTE) hearing instruments support open or closed configurations.

ReSound's SmartRange™ dual processing platform enables Surround Sound by ReSound™ sound quality.

The 3rd generation 2.4 GHz wireless functionality of the SmartRange platform features Bluetooth® 4.0, allowing the hearing instruments to communicate with each other and to connect to iPhone®, iPad® and iPod touch®. ReSound LiNX² also supports ReSound's full line of ReSound Unite™ accessories. The 77 model features telecoil and Direct Audio Input (DAI).

All ReSound LiNX² BTE hearing instruments are iSolate™ nanotech-coated for optimum durability.


Model	LS977-DW LS977-DWT	LS777-DW LS777-DWT	LS577-DW LS577-DWT
Device Features			
Battery size	13		
Colors available	14 (10 standard + 4 as replacement kits)		
Functional Features			
Fully flexible programs	4	4	4
Synchronized push button	●	●	●
Synchronized volume control	●	●	●
SmartStart™	●	●	●
PhoneNow™	●	●	●
Comfort Phone™	●	●	●
Ear-to-Ear communication	●	⊙	○
Direct audio streaming (Made for iPhone)	●	●	●
ReSound Unite™ TV Streamer 2, Remote Control 2, Phone Clip+, Mini Microphone	●	●	●
ReSound Control™ app (Phone Clip+ required)	●	●	●
ReSound Smart™ app	●	●	●
Audiological Features			
WARP compression - number of channels	17	14	12
Environmental Classifier	●	●	●
Binaural Directionality™ II	●		
Spatial Sense™	●		
Binaural Directionality™		●	
Directional Mix Processor	●	●	●
-Adjustable directional mix	●		
Natural Directionality™ II	●	●	●
Synchronized SoftSwitching™	●	●	
Softswitching™			●
Autoscope Adaptive Directionality™	●		
Multiscope Adaptive Directionality™		●	
Adaptive Directionality™			●
Binaural Environmental Optimizer™ II	●		
Environmental Optimizer		●	
NoiseTracker™ II	●	⊙	○
Expansion	●	⊙	○
Windguard™	●	⊙	○
Sound Shaper	●	●	●
DFS Ultra™ II	●	●	●
-Music Mode™	●	●	●
Auto DFS™	●	●	●
Synchronized Acceptance Manager	●	●	●
Tinnitus Sound Generator	●	●	●
Fitting Features			
Fitting software Aventa 3.8 or higher	●	●	●
Onboard Analyzer™ II	●	●	●
In Situ Audiometry	●	●	●
Wireless fitting with Airlink™ 2	●	●	●

○ Basic

⊙ Advanced

● Ultimate

Fitting Range



ReSound LiNX² is compatible with iPhone 6, iPhone 6 Plus, iPhone 5s, iPhone 5c, iPhone 5, iPad Air 2, iPad Air, iPad (4th generation), iPad mini 3, iPad mini 2, iPad mini with Retina display, iPad mini and iPod touch (5th generation) using iOS 7.X or later. Apple, the Apple logo, iPhone, iPad and iPod touch are trademarks of Apple Inc., registered in the U.S. and other countries.



400352000-GB-15.04-RevC

ReSound A/S
Lautrupbjerg 7
DK-2750 Ballerup, Denmark
Tel.: +45 45 75 11 11
Fax: +45 45 75 11 19
www.resound.com

United Kingdom
GN ReSound Ltd.
Kirtlington Business Centre
Portway
Kirtlington
Oxon OX5 3JA
Tel.: +44 1869 352 800
Fax: +44 1869 343 466
www.gnresound.co.uk

Australia
GN ReSound Pty. Ltd.
Unit R1 Regent Park Estate
391 Park Road
Regent Park NSW 2143
Tel.: 02 9743 9707
Fax: 02 9743 7472
Free call number: 1800 658 955
www.gnresound.com.au

New Zealand
GN ReSound (NZ) Ltd.
Ground Floor, North Entrance
4 Fred Thomas Drive
Takapuna
Auckland, 0622
Tel.: (free) 0800 900 126
Fax: (free) 0800 007 695
www.gnresound.co.nz



Technical Specifications

		LS77-DWT		
		IEC 60118-0 IEC 711 Ear simulator	IEC 60118-7 ANSI S3.22 2cc coupler	
Reference test gain (60 dB SPL input)	1600 Hz/HFA	45	38	dB
Full-on gain (50 dB SPL input)	Max.	62	51	dB
	1600 Hz/HFA	54	48	
Maximum output (90 dB SPL input)	Max.	131	127	dB SPL
	1600 Hz/HFA	121	116	
Total harmonic distortion	500 Hz	0.5	0.2	%
	800 Hz	0.5	0.2	
	1600 Hz	0.9	0.6	
Telecoil sensitivity (1 mA/m input)	Max.	94		dB SPL
HFA - SPLIV @ 31.6 mA/m (ANSI)	HFA		100	
Full-on telecoil sensitivity @ 1 mA/m	1600 Hz/HFA	87	80	
Equivalent input noise		25	22	dB SPL
Frequency range (DIN 45605/ANSI)		100-6920	100-6810	Hz
Current drain		1.2	1.2	mA

Data in accordance with IEC 60118-0, IEC 60118-7 and ANSI S3.22-2009; supply voltage 1.3 V.

Technical Specifications

		LS77-DW		
		IEC 60118-0 IEC 711 Ear simulator	IEC 60118-7 ANSI S3.22 2cc coupler	
Reference test gain (60 dB SPL input)	1600 Hz/HFA	48	43	dB
Full-on gain (50 dB SPL input)	Max.	66	57	dB
	1600 Hz/HFA	58	53	
Maximum output (90 dB SPL input)	Max.	134	124	dB SPL
	1600 Hz/HFA	126	121	
Total harmonic distortion	500 Hz	0.4	0.4	%
	800 Hz	1.4	0.8	
	1600 Hz	0.9	0.7	
Telecoil sensitivity (1 mA/m input)	Max.	98		dB SPL
HFA - SPLIV @ 31.6 mA/m (ANSI)	HFA		105	
Full-on telecoil sensitivity @ 1 mA/m	1600 Hz/HFA	90	85	
Equivalent input noise		25	20	dB SPL
Frequency range (DIN 45605/ANSI)		100-6560	100-6140	Hz
Current drain		1.2	1.2	mA













Data in accordance with IEC 60118-0, IEC 60118-7 and ANSI S3.22-2009; supply voltage 1.3 V.

Patents pending

All specifications are subject to change without notice

Patents pending

All specifications are subject to change without notice



Notes:
O.E.S. = Occluded Ear Simulator
2cc = 2 cm³ coupler
Pi = Acoustic input signal

Basic settings:
Full-on Gain, Reference Test Gain
MPO = Maximum Power Output
Maximum Band Width

Measured according to IEC 60 118-0 1983, amendment 1994; at 1.3 V, impedance 6.2 ohms and 23°C on O.E.S. according to IEC711 1981, resp on 2cc according to IEC60118-7 2nd edition 2005 and ANSI S3.22-2009 (HFA average calculated at 1000 Hz, 1600 Hz and 2500 Hz; 0 dB SPL sound pressure equals 20µPa). All measurements without DSP features activated unless indicated otherwise.

ReSound

rediscover hearing